11 Publication number:

**0 348 310** A3

**(2)** 

## **EUROPEAN PATENT APPLICATION**


- 21 Application number: 89420204-3
- 2 Date of filing: 12.06.89

(s) Int. Cl.5: B32B 27/00, B32B 27/16, B32B 31/10, B32B 33/00

- Priority: 23.06.88 US 210280
- ② Date of publication of application: 27.12.89 Bulletin 89/52
- Designated Contracting States:
   BE CH DE FR GB LI NL SE
- Date of deferred publication of the search report: 14.11.90 Bulletin 90/46
- Applicant: EASTMAN KODAK COMPANY (a New Jersey corporation) 343 State Street Rochester New York 14650(US)
- (7) Inventor: Smith, Thomas M. c/o EASTMAN KODAK COMPANY
  Patent Department 343 State Street
  Rochester New York 14650(US)
- Representative: Parent, Yves et al Kodak-Pathé Département Brevets et Licences Centre de Recherches et de Technologie Zone Industrielle F-71102 Chalon-sur-Saône Cédex(FR)
- Abrasion-resistant protective laminates.
- Multi-layer sheet materials useful as protective laminates for application to substrates, such as photographic elements, which require the protection of an abrasion-resistant material, are comprised of a strippable carrier (10), an abrasion-resistant layer (12) which overlies the carrier, a structural interlayer (14) which overlies the abrasion-resistant layer, and an adhesive layer (16) which overlies the structural interlayer. The structural interlayer is very thin in relation to the thickness of the carrier, and is permanently bonded to one surface of the abrasion-resistant layer, whereas the carrier is releasably bonded

to the other surface of the abrasion-resistant layer so as to permit it to be stripped away after it has served its purpose. A process for manufacturing the multi-layer sheet material comprises the steps of advancing the carrier in web form through a coating station at which it is coated with a layer of liquid composition that is curable to a solid form; laminating the structural interlayer to the coated-surface of the carrier; curing the liquid layer in situ to a solid form to thereby form an abrasion-resistant layer; and applying an adhesive layer over the surface of the structural interlayer.







## **EUROPEAN SEARCH REPORT**

EP 89 42 0204

Category	Citation of document with of relevant parties	ndication, where appropriate, assages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL4)
A,D	US-A-4337107 (ESHLEMAN	)	1, 2,	B32B7/06
,-	•	column 6, line 13; figure	5-7, 9,	B32B27/00
	*		14	B32B27/16
				B32B31/10
A, D	US-A-4077830 (FULWILER	)	1, 2	B32B33/00
	* column 3, lines 8 -	64; figure 1 * 		B05D1/00
A,D	US-A-4581267 (MILLER)		1. 2	
	* column 2, line 48 -	column 3, line 20 *		
	* column 4, lines 2 -			
	* column 4, lines 27 -	33; figure 1 *		
A		E EMBALLAGE IND. VAN LEER)	1, 14	
	* page 1, lines 15 - 3 * page 2, lines 25 - 2			
	* page 2, lines 25 - 28  * page 3, lines 4 - 14			
	* page 8, lines 17 - 3			
	page of Times 17	· 		
				TECHNICAL FIELDS SEARCHED (Int. Cl.4)
				B32B
			1 1	G03F1
				G03C11
				B05D1
				·
, <sup>1.</sup>			** 12.	• • •
··· .				
İ				
	The present search report has been present search	Date of completion of the search	لـــــا	Exeminer
THE HAGUE		12 SEPTEMBER 1990		
X : part Y : part	CATEGORY OF CITED DOCUME icutarly relevant if taken alone icutarly relevant if combined with an ment of the same category	E : earlier patent doc after the filing da	cument, but publi ate n the application	invention shed on, or